



Rainbow Road Bridge Replacement Project

Carter Lautner, P.Eng., Ryan MacPhee, C.E.T., and Olivia Lautner, P.Eng

Project Team

Carter Lautner, P.Eng.
Project Engineer
Associated Engineering



Ryan MacPhee, C.E.T.
Technologist
Associated Engineering



Olivia Lautner, P.Eng.
Project Manager
Volker Stevin Highways



Introduction

- Location: Chestermere, Alberta
- Project Delivery Model: Design-Bid-Build (DBB)
- Key Project Stakeholders:
 - Consultant: Associated Engineering
 - Prime Contractor: Volker Stevin Highways (Bridge Division)
 - Owner: City of Chestermere
 - Other Affiliations: Western Headworks Canal, Canadian National Railway, Epcor, Various Utility Companies
- Collaboration Strategy: Focus on consultant-contractor-owner partnership to address daily challenges and foster innovation



Introduction

- Location: Chestermere, Alberta
- Project Delivery Model: Design-Bid-Build (DBB)
- Key Project Stakeholders:
 - Consultant: Associated Engineering
 - Prime Contractor: Volker Stevin Highways (Bridge Division)
 - Owner: City of Chestermere
 - Other Affiliations: Western Headworks Canal, Canadian National Railway, Epcor, Various Utility Companies
- Collaboration Strategy: Focus on consultant-contractor-owner partnership to address daily challenges and foster innovation



Introduction – Existing Structure



Backwall width = deck width plus 13' - 0"

5' - 6" Deck width to be specified (Roadway) 5' - 6"

Shoulder

Bridge

Tie wires

5" plank sheathing

File spacing as specified

12"x14" cap at abutment.
12"x12" may be used for
20' span & 21' clear roadway.

A — A'



Introduction – New Structure




Introduction – New Structure




Introduction – New Structure Cross Section

- 31.5 m single span 1600 NU girders, five girder lines
- Semi-integral abutment, cast-in-place concrete pile foundation



Introduction – New Structure Plan



Introduction – Additional Project Scope

- Roadway re-alignment and pathway tie ins
- Stormwater tie in manholes and catch basin into existing infrastructure. Drain troughs not suitable for Western Headworks Canal (WHC)
- Shallow Utilities Relocation – Fortis Overhead Power
- Alberta Irrigation Land Access to WHC
- Replacement bridge structure – pedestrian connectivity




Project Objectives and Timelines

- Primary Goal: Timely replacement of the Rainbow Road Bridge (a main thoroughfare in the City) to meet the City's completion deadline
- Tight Schedule: Highlighting the importance of the City's deadline and how it influenced decision making



Project Objectives and Timelines



Design Challenges and Solutions

- Tight Urban Area
- Consultant Design Challenges:
 - Foundation design dictated the abutment type
 - Unreliable as built records
 - Sanitary sewer right through the design alignment for the roadway
 - Pipe alignment on horizontal curve
 - Robotic LiDAR survey required to confirm alignment and offset to bridge foundation piles



Construction Challenges and Solutions

- Challenge: Deep Sanitary Line Survey
 - Solutions:
 - Conduct thorough site investigation
 - Confined space entry support
 - Survey during low flow conditions
 - Flush line
 - Outcome: Confirmed location of the 1200 mm HDPE-lined sanitary trunk



Construction Challenges and Solutions

- Challenge: Deep Sanitary Line Survey
 - Solutions:
 - Conduct thorough site investigation
 - Confined space entry support
 - Survey during low flow conditions
 - Flush line
 - Outcome: Confirmed location of the 1200 mm HDPE-lined sanitary trunk



Construction Challenges and Solutions

- Challenge: Geometric Constraints for Girder Installation
 - Issue: Limited space for equipment in urban area, load restricted bridge, and limited road closures allowed
 - Solution:
 - Tandem lift
 - Pre-erection activities at EPCOR facility
 - Outcome: Installed NU girders safely and efficiently, minimizing public disruption



Construction Challenges and Solutions

- Challenge: Geometric Constraints for Girder Installation
 - Issue: Limited space for equipment in urban area, load restricted bridge, and limited road closures allowed
 - Solution:
 - Tandem lift
 - Pre-erection activities at EPCOR facility
 - Outcome: Installed NU girders safely and efficiently, minimizing public disruption



Construction Challenges and Solutions

- Challenge: Fall Protection
 - Issue: Varied fall heights (3 m - 4 m) required adaptive safety systems
 - Solutions:
 - Man-Lifts with Lanyard: Secured workers during crane hand-off
 - Horizontal Lifeline Systems: Protected workers during deck formwork installation (4 m)
 - Rebar and Self Retracting Lifelines: Anchored workers during diaphragm and bracing installation (<4 m)
 - Outcome: Workers protected against fall risks



Construction Challenges and Solutions

- Challenge: Fall Protection
 - Issue: Varied fall heights (3 m - 4 m) required adaptive safety systems
 - Solutions:
 - Man-Lifts with Lanyard: Secured workers during crane hand-off
 - Horizontal Lifeline Systems: Protected workers during deck formwork installation (4 m)
 - Rebar and Self Retracting Lifelines: Anchored workers during diaphragm and bracing installation (<4 m)
 - Outcome: Workers protected against fall risks



Construction Challenges and Solutions

- Challenge: Adhering to Completion Deadlines
 - Issue: Need to meet the tight timeline
 - Solution:
 - Deployed two piling rigs at each abutment to accelerate cast-in-place concrete pile installation



Construction Challenges and Solutions

- Challenge: Adhering to Completion Deadlines
 - Issue: Need to meet the tight timeline
 - Solution:
 - Deployed two piling rigs at each abutment to accelerate cast-in-place concrete pile installation



Construction Challenges and Solutions

- Challenge: Adhering to Completion Deadlines
 - Issue: Need to meet the tight timeline
 - Solution:
 - Deployed two piling rigs at each abutment to accelerate cast-in-place concrete pile installation
 - Poured all cast-in-place abutment components monolithically



Construction Challenges and Solutions

- Challenge: Adhering to Completion Deadlines
 - Issue: Need to meet the tight timeline
 - Solution:
 - Deployed two piling rigs at each abutment to accelerate cast-in-place concrete pile installation
 - Poured all cast-in-place abutment components monolithically



Construction Challenges and Solutions



Construction Challenges and Solutions

- Challenge: Proximity to Active CN Spur Line
 - Issue: Transporting 100 ft girders over active train tracks required precise coordination.
 - Solution:
 - Early and continuous communication with CN Rail
 - Secured green lights for track crossings, ensuring no train activity during girder delivery



Construction Challenges and Solutions

- Challenge: Deck Finishing Approach
 - Issue: Traditional finishing machines and standard work bridges cannot maneuver around obstacles like barrier reinforcing steel.
 - Solution:
 - Gomaco Deck Finishing Machine - for deck slab



Construction Challenges and Solutions

- Challenge: Deck Finishing Approach
 - Issue: Traditional finishing machines and standard work bridges cannot maneuver around obstacles like barrier reinforcing steel.
 - Solution:
 - Gomaco Deck Finishing Machine - for deck slab



Construction Challenges and Solutions

- Challenge: Deck Finishing Approach
 - Issue: Traditional finishing machines and standard work bridges cannot maneuver around obstacles like barrier reinforcing steel.
 - Solution:
 - Gomaco Deck Finishing Machine - for deck slab
 - Roller Screed - for sub-sidewalk deck slab



Construction Challenges and Solutions

- Challenge: Deck Finishing Approach
 - Issue: Traditional finishing machines and standard work bridges cannot maneuver around obstacles like barrier reinforcing steel.
 - Solution:
 - Gomaco Deck Finishing Machine - for deck slab
 - Roller Screed - for sub-sidewalk deck slab



Construction Challenges and Solutions

- Challenge: Deck Finishing Approach
 - Issue: Traditional finishing machines and standard work bridges cannot maneuver around obstacles like barrier reinforcing steel.
 - Solution:
 - Gomaco Deck Finishing Machine - for deck slab
 - Roller Screed - for sub-sidewalk deck slab
 - Custom Work Bridges - accommodate cast-in-place barriers not adjacent to the rails / supports



Construction Challenges and Solutions

- Challenge: Deck Finishing Approach
 - Issue: Traditional finishing machines and standard work bridges cannot maneuver around obstacles like barrier reinforcing steel.
 - Solution:
 - Gomaco Deck Finishing Machine - for deck slab
 - Roller Screed - for sub-sidewalk deck slab
 - Custom Work Bridges - accommodate cast-in-place barriers not adjacent to the rails / supports



Project Impact and Concluding Remarks



Thank you! Questions?

